

Serviceing What We Sell



42 SERIES



GAS DRIVEN, OIL FIRED SELF CONTAINED PRESSURE WASHER | Specifications:

GENERAL					ENGINE/BURNER SYSTEM							DIMENSIONS/WEIGHT			
Model	GPM	PSI	HP	Drive	Volt	Engine	Engine Start	Fuel Engine/Burner	BTU	Stack Size	L	W	H	Lb	
42-430H / 42-430GH	4	3000	13	Belt	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	725/850	
42-430H-C / 42430GH-C	4	3000	13	Clutch	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	740/865	
42-440V / 42-440GV	4	4000	16	Belt	12/110	Vanguard	Electric	Gas/Oil	384,000	8"	43"	34"	43"	750/850	
42-440H / 42-440GH	4	4000	20	Belt	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	750/850	
42-530V / 42-530GV	5	3000	16	Belt	12/110	Vanguard	Electric	Gas/Oil	465,000	8"	43"	34"	43"	750/820	
42-530V-C / 42-530GV-C	5	3000	16	Clutch	12/110	Vanguard	Electric	Gas/Oil	465,000	8"	43"	34"	43"	765/835	
42-535H / 42-535GH	5	3500	20	Belt	12/110	Honda	Electric	Gas/Oil	465,000	8"	43"	34"	43"	800/865	
42-530H-C / 42-530GH-C	5	3000	20	Clutch	12/110	Honda	Electric	Gas/Oil	465,000	8"	43"	34"	43"	815/880	
42-830V / 42-830GV	8	3000	23	Belt	12/110	Vanguard	Electric	Gas/Oil	547,000	8"	43"	34"	43"	1015/1080	
42-830V-C / 42-830GV-C	8	3000	23	Clutch	12/110	Vanguard	Electric	Gas/Oil	547,000	8"	43"	34"	43"	1015/1080	

Features (not shown on breakout):

- Quick Couple Stainless Steel Nozzles
- ASTM A53 Schedule 80 Steel Heating Coil
- Trigger Gun Control
- Variable Pressure Wand (42-430/42-530)
- Wire Braid Discharge Hose
- Low Oil Engine Protection
- Water Separating Fuel Filter
- Low Water Shutoff Protection
- Automatic Electric Burner Ignition

- Extended Engine Oil Drain (Vanguard)
- Auxiliary Gasoline Tank (42-440/42-530/42-830)
- Shock Mount Plastic Battery Box
- Stainless Steel Control Panel

12V H Models

- High Amp Charging System
- 12V Ignition System
- Downstream Chemical Injection

110V GH Models

- Calibrated Detergent Mixing Valve
- High Pressure Soap
- Circuit Breaker Protected
- Stainless Steel Float Tank



A Closer Look at the Features:

Hour Meter
Allows you to keep track for periodic maintenance.

Adjustable Temp. Control
For your precise temp. control.

Electric Start
Allows for quick & easy operation without pull cord strain.

Vanguard/Honda Engines
Time proven dependability.

Shock Absorbing Engine Base
Dampens vibrations reducing engine & frame fatigue, prolonging life.

Poly Fuel Tank
Prevents corrosion saving costly replacement.

Industrial Strength Triplex Pump
Built strong to handle the toughest demands.

Optional Clutch Drive
Save money by lengthening the life of your pump.

Pressure Relief Valve
Prevents injury & cost due to an over-pressurized system.

Optional Generator
Enables your use of a 110V burner.

Durable Powder Coated Heavy Duty Roll Cage Frame
For years of great looking service & protecting the unit's internal parts.

Exclusive Coil Design
Heats water quicker & more efficiently.

Stainless Steel Combustion Chamber & Side Panels
Maintenance free, durable protection.

High Efficiency Burner
Conserve fuel & your dollars.

Notes:

